

TR, TR-T & TR-TS

PRODUCT FEATURES & BENEFITS

END CAP:

- Positive Snap Lock Seal Design; Weather Seal™ Plug
- Attached to head to prevent loss
- Weather resistant closure

RELEASE TOOL:

- Standard SAE threads – low torque wind off
- Convenient tool storage in center case adapter side pocket

STEEL HEAD:

- Taper-head design for tight space installations
- Patented tamper resistant design (US Patent #5,067,391)
- Protected by heat-cured epoxy finish inside and out

EXTERNAL BREATHER TUBE SYSTEM:

- Seals power spring chamber against contaminants and corrosive outside air (TR-T and TR-TS Models only)

POWER SPRING PISTON AND GUIDE:

- Low friction fluted aluminum piston aligns through patented steel guide, prevents binding and ensures full release from applied position
- Protected by heat-cured epoxy finish (TR-TS Model only)

POWER SPRING:

- Heat-fused epoxy coated protection; meets or exceeds all OEM performance standards
- Cycle Test certified to OEM vehicle specification

CENTER CASE ADAPTER PUSH-ROD AND GUIDE:

- Aluminum hard coat finish with oversize push plates for maximum diaphragm support and alignment
- Surface finish to retain lubricants
- Two (2) non-ferrous guides to prevent metal-to-metal contact and wear from side loading
- Multi-lipped pressure activated seal – MGM Brakes exclusive; with wiping edge and lube retention grooves to ensure positive air seal at full range of stroke

RETURN SPRINGS:

- Special conical shaped full release design
- Coated for maximum cycle life protection
- Protected by heat-cured epoxy finish (TR-TS Model only)

TR



TR-T



TR-TS



MGM Brakes

A Division of Indian Head Industries, Inc.

Form No. 5023

TR, TR-T & TR-TS

PRODUCT FEATURES & BENEFITS

NON-PRESSURE CHAMBER/MOUNTING BASE:

- Heavy duty 9 gauge (.150) epoxy coated steel, specially formed for added strength; except Type 30 which is 8 gauge (.172)
- Pressed in mounting studs, serrated base connection plus internal reinforcing pads on all 9 gauge NPC housings
- Prevailing torque nuts with hardened flat washers
- Reverse chamber bridge designed bottom for positive axle bracket positioning

EPOXY FINISH PROTECTION:

- Flexible coating that will not crack, chip or peel in severe service environments
- Complete encapsulation to prevent rust or corrosion
- Epoxy powder electrostatically applied and heat-fused to component

SERVICE PISTON ROD:

- True-weld connection to piston plate
- Fully threaded for universal slack adjuster installation requirements

CENTER CASE ADAPTER HOUSING:

- Alloy 360 aluminum - more magnesium, less copper content for increased corrosion resistance
- Bottom sealing groove for service diaphragm connection
- Integral release tool holder
- Protected by heat-cured epoxy finish inside and out (TR-TS Model only)

STROKE ALERT

INDICATOR:

- High visibility orange paint on black epoxy coated push-rod
- Indicates push-rod stroke at 70-80% of recommended readjustment dimension

DIAPHRAGMS:

- Heavy-duty nylon-reinforced
- Premium formulation for low temperature performance
- Perimeter seal lip ensures air tight assembly

CENTER HOLD SHIELD:

- Two piece design moves with service piston
- Shields entrance to granular contaminants
- Permits visual inspection of stroke alert

TR-LP3



TR-LP3T



TR-LP3TS



A Division of Indian Head Industries, Inc.
www.mgmbrakes.com

Form 5023
©1999 MGM Brakes - Revised 9-2011
All Rights Reserved.
Printed in U.S.A.