

TR-TS Series

Severe Service Spring Brakes



**BUILT TOUGH
FOR RUGGED JOBS**



**EPOXY-COATED
FOR ADDED
PROTECTION**



MGM Brakes

Form No. 5029

TR-TS Model Spring Brakes



**Epoxy-Coated Components
for Added Protection**

**Designed for Severe Service
Operating Environments Including:**

- Acids & Liquid Corrosives
- Petroleum Products
- Ready - Mix Concrete
- Dry Bulk Industrial Chemicals
- Livestock & Poultry
- Salt
- Toxic Waste
- Fertilizer
- Refuse Collection

P/N Series	3538	3528	3531	3532	3536	3526	3533	3523	3535	3527	3534
Model	TR2424LTS	TR2430LTS	TR3030TS	TR3036TS	TR3636TS	TR2430LTSHD	TR3030TSHD	TR2430LP3TS	TR3030LP3TS	TR2430LP3TSHD	TR3030LP3TSHD
Size	2424	2430	3030	3036	3636	2430	3030	2430	3030	2430	3030
Stroke	2.50"	2.50"	2.50"	2.50"	3.00"	2.50"	2.50"	3.00"	3.00"	3.00"	3.00"
P/N Combination	3538051	3528051	3531051	3532051	3536051	3526051	3533051	3523051	3535051	3527051	3534051
P/N Single/Piggyback	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
P/N Piggyback Plus Kit	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Wt. Combination (Lbs.)	16.6	18.5	20.0	26.5	30.8	18.6	19.9	19.3	20.1	19.5	20.4
Wt. Single (Lbs.)	9.5	11.6	11.6	18.3	20.2	11.7	11.5	11.7	11.5	11.5	11.7
A	8.52	9.04	9.04	9.86	11.13	9.04	9.04	10.19	9.99	10.19	9.99
B	6.36	6.91	6.66	7.52	8.38	6.91	6.66	7.81	7.61	7.81	7.61
C	7.38	7.38	8.31	8.31	9.25	7.38	8.31	7.38	8.32	7.38	8.32
D	7.34	8.21	8.21	9.18	9.18	8.21	8.21	8.21	8.21	8.21	8.21
E	4.75"										
F	5/8" - 11UNC										
G	5/8" - 18UNF										
Inlets	3/8" - NPTF										
X - Min. (caged position)	8.00"										

Note: All dimensions shown in inches and are subject to design change.



- Heavy-duty 8-gauge steel non-pressure chamber
- Heavy impact-resistant steel head
- Epoxy-coated inside and out
- External-breather tube design
- Internal "sliding stone shield"



Available from:



A Leader in Truck & Bus Safety—Worldwide.



A Division of Indian Head Industries, Inc.

www.mgmbrakes.com

Form No. 5029 - Rev. 10/2010
All Rights Reserved.

©1996 MGM Brakes
Printed in U.S.A.