

TR-TS Series

Severe Service Spring Brakes



**BUILT TOUGH
FOR RUGGED JOBS**



**EPOXY-COATED
FOR ADDED
PROTECTION**



MGM Brakes

Form No. 5029

TR-TS Model Spring Brakes



**Epoxy-Coated Components
for Added Protection**

**Designed for Severe Service
Operating Environments Including:**

- Acids & Liquid Corrosives
- Petroleum Products
- Ready - Mix Concrete
- Dry Bulk Industrial Chemicals
- Livestock & Poultry
- Salt
- Toxic Waste
- Fertilizer
- Refuse Collection

| P/N Series | 3538 | 3528 | 3531 | 3532 | 3536 | 3526 | 3533 | 3523 | 3535 | 3527 | 3534 |
|---------------------------|--------------|-----------|----------|----------|----------|-------------|------------|-------------|-------------|---------------|---------------|
| Model | TR2424LTS | TR2430LTS | TR3030TS | TR3036TS | TR3636TS | TR2430LTSHD | TR3030TSHD | TR2430LP3TS | TR3030LP3TS | TR2430LP3TSHD | TR3030LP3TSHD |
| Size | 2424 | 2430 | 3030 | 3036 | 3636 | 2430 | 3030 | 2430 | 3030 | 2430 | 3030 |
| Stroke | 2.50" | 2.50" | 2.50" | 2.50" | 3.00" | 2.50" | 2.50" | 3.00" | 3.00" | 3.00" | 3.00" |
| P/N Combination | 3538051 | 3528051 | 3531051 | 3532051 | 3536051 | 3526051 | 3533051 | 3523051 | 3535051 | 3527051 | 3534051 |
| P/N Single/Piggyback | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| P/N Piggyback Plus Kit | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| Wt. Combination (Lbs.) | 16.6 | 18.5 | 20.0 | 26.5 | 30.8 | 18.6 | 19.9 | 19.3 | 20.1 | 19.5 | 20.4 |
| Wt. Single (Lbs.) | 9.5 | 11.6 | 11.6 | 18.3 | 20.2 | 11.7 | 11.5 | 11.7 | 11.5 | 11.5 | 11.7 |
| A | 8.52 | 9.04 | 9.04 | 9.86 | 11.13 | 9.04 | 9.04 | 10.19 | 9.99 | 10.19 | 9.99 |
| B | 6.36 | 6.91 | 6.66 | 7.52 | 8.38 | 6.91 | 6.66 | 7.81 | 7.61 | 7.81 | 7.61 |
| C | 7.38 | 7.38 | 8.31 | 8.31 | 9.25 | 7.38 | 8.31 | 7.38 | 8.32 | 7.38 | 8.32 |
| D | 7.34 | 8.21 | 8.21 | 9.18 | 9.18 | 8.21 | 8.21 | 8.21 | 8.21 | 8.21 | 8.21 |
| E | 4.75" | | | | | | | | | | |
| F | 5/8" - 11UNC | | | | | | | | | | |
| G | 5/8" - 18UNF | | | | | | | | | | |
| Inlets | 3/8" - NPTF | | | | | | | | | | |
| X - Min. (caged position) | 8.00" | | | | | | | | | | |

Note: All dimensions shown in inches and are subject to design change.



- Heavy-duty 8-gauge steel non-pressure chamber
- Heavy impact-resistant steel head
- Epoxy-coated inside and out
- External-breather tube design
- Internal "sliding stone shield"



Available from:



A Leader in Truck & Bus Safety—Worldwide.



A Division of Indian Head Industries, Inc.

www.mgmbrakes.com

Form No. 5029 - Rev. 10/2010
All Rights Reserved.

©1996 MGM Brakes
Printed in U.S.A.